

## CLBC Series



### FEATURES & BENEFITS

- Streamlined design allows prevention of build-up of dust and foreign material on the fitting
- Glass cover allows easy cleaning
- Ideal for applications demanding high corrosion resistance
- Unique heat dissipation design
- IP67 rated
- 10 years limited warranty
- UL/ CUL/ LM79/ CE/ RoHS

A modern yet functional take on the widely popular high bay light for warehouses and food processing plants. The CLBC is a versatile and rugged designed light for use in environmentally demanding applications.

### TECHNICAL PARAMETERS

Power	150/200W
Input	90-305 VAC
PF	>0.95
THD	< 15%
L70	>50,000H
Operating Temperature	-40°C ~ +50°C
Efficacy	140-160lm/W
ANSI CCT	4000K/5000K
Min CRI	70* or 80
IP Rating	IP67
SPD	Optional
DALI	/
1-10V	Optional
Photocell	/
Smart Control	/
Optic (IESNA)	Type V
Color Options	Grey

\* Standard



### ORDERING INFORMATION

Example : BBC200-T5G-50K-GR-00

MODEL (Nominal Power)	OPTIC LENS	CCT (ANSI)	OPTIONAL COLOR	LIGHTING CONTROL	ACCESSORY INFO
90-305VAC					
CLBC150 CLBC200	T5G	40K ★ 50K	GR	00 Not required 05 1-10V dimming	10KA/20KA Surge Protection Device

★ Regularly stocked item